



Ifzo Equipment Co., Ltd

MISUMI 51208 Single Thrust Ball Bearings

Bearing No. 51208

| | |
|-------------------------------------|--------------------------|
| Days to Ship | 6 Days or more |
| RoHS | 6 |
| I.D.(\varnothing) | 40 |
| O.D.(\varnothing) | 68 |
| Width | 19 mm |
| Basic Dynamic Load Rating(N) | 47500 |
| Max. Allowed rpm(rpm) | 2800 |
| Basic Load Rating, Static Rating(N) | 98500 |
| Holder Symbol | No |
| Types | Flat Surface Washer Type |
| Type | Thrust Ball |
| Inner/Outer Ring Material | Steel |
| Bearing Style | Open Type |
| Outer Ring Shape | Flat |
| Precision | Grade 0 |
| Specifications, Environment | Standard |
| Load Direction | Thrust |
| Outer Ring | With Outer Ring |
| Number of Raceway Ring Rows | Single Row |
| Size Standards | Metric System |
| Rolling Element Material | Steel |
| Retainer Type | Punching |
| Precision Grade Symbol | No |
| Type | Thrust Ball |
| | |

51208 Bearing 2D drawings and 3D CAD models



Ifzo Equipment Co., Ltd

| | |
|-----------------------------|-----------------|
| Inner/Outer Ring Material | Steel |
| Bearing Style | Open Type |
| Outer Ring Shape | Flat |
| Precision | Grade 0 |
| Specifications, Environment | Standard |
| Load Direction | Thrust |
| Outer Ring | With Outer Ring |
| Number of Raceway Ring Rows | Single Row |
| Size Standards | Metric System |
| Rolling Element Material | Steel |
| Retainer Type | Punching |
| Precision Grade Symbol | No |
| d | 40 |
| D | 68 |
| B | 19 |
| Specifications/Environment | Standard |
| Specifications/Environment | Standard |